

## 0429P DANPALON ROOFING - GLAZED

**Branded worksection**

This branded worksection *Template* has been developed by NATSPEC in conjunction with **Danpal Australia Pty Limited** (the Product Partner) and may be used whilst the Product Partner is licensed to distribute it. The copyright remains with NATSPEC. As with all NATSPEC worksections, it is the responsibility of the user to make sure it is completed appropriately for the project. The user should also review its applicability for local conditions and regulations. Check [www.natspec.com.au](http://www.natspec.com.au) for the latest updated version.

**Worksection abstract**

This branded worksection *Template* is applicable to DANPALON roof glazing and glazed awning systems by Danpal Australia Pty Limited.

**How to use this worksection**

Customise this worksection *Template* for each project. See [A guide to NATSPEC worksections \(www.natspec.com.au\)](http://www.natspec.com.au) for information on *Template* structure, word styles and completing a worksection.

**Related material located elsewhere in NATSPEC**

If a listed worksection is not part of your subscription package and you wish to purchase it, contact NATSPEC.

Related material may be found in other worksections, including:

- 0193 *Building access safety systems*.
- 0341 *Structural steelwork*.
- 0342 *Light steel framing* for the subframe.
- 0343 *Tensioned membrane structures* for suspended fabric roofing.
- 0411 *Waterproofing - external and tanking* for membrane roofs.
- 0461 *Glazing* for glass roofing and skylights.
- 0471 *Thermal insulation and pliable membranes* for thermal insulation, thermal break strips and vapour permeable membranes.
- 0552 *Metalwork - fabricated* for ladders, platforms and balustrades.
- 0802 *Hydraulic design and install* for stormwater and rainwater storage systems.

Each of the following worksections contains a single roofing system and may be used where appropriate in addition to this worksection:

- 0423 *Roofing - profiled sheet metal*.
- 0424 *Roofing - seamed sheet metal*.
- 0425 *Roofing - shingles and shakes*.
- 0426 *Roofing - slate*.
- 0427 *Roofing - tiles*.
- 0428 *Roofing - insulated panel systems*.

Related branded worksections include:

- 0434p *DANPALON translucent facade cladding*.

**Documenting this and related work**

You may document this and related work as follows:

- Locate the extent of roofing types, accessories, and finishes on drawings to your office documentation policy.
- Penetrations: Show on the drawings the location and extent of penetrations for services and structural elements including flashing details.
- Document the structural support system to your office documentation policy.
- Coordinate the glazed roofing with any supporting structure and framing designed by a structural engineer.
- Show rooftop walkways, ladders and access systems on the drawings. Document in 0193 *Building access safety systems* if part of a complete building access installation to AS 1657 (2018).
- Contact DANPALON for limits of panel length and span tables.
- For guidelines on the design of roofs in snow areas, see AS/NZS 1170.3 (2003) and HB 106 (1998).
- For information on air, moisture and condensation, see NATSPEC TECHnote DES 004.

The *Normal* style text of this worksection may refer to items as being documented elsewhere in the contract documentation. Make sure they are documented.

Search [acumen.architecture.com.au](http://acumen.architecture.com.au), the Australian Institute of Architects' practice advisory subscription service, for notes on the following:

- Birds and buildings.
- Guarantees and warranties.
- Site planning and design for bushfire.
- Waterproofing.

#### Specifying ESD

The following may be specified by including additional text:

- Design for disassembly. DANPALON panels can be dismantled and re-used elsewhere.
- High performance roofing systems to extend building service life.
- High thermal performance to reduce heating/cooling load.
- Recycled material content.
- Recycling of construction scrap materials or offcuts. Polycarbonate is 100% recyclable.

Refer to NATSPEC TECHreport TR 01 on specifying ESD.

## 1 GENERAL

DANPALON is a patented glazing snap-connection system with concealed fasteners that provides for 100% watertightness; free structural and thermal movement within a flexible system; structural properties that allow for a significantly reduced substructure; quick and easy installation; the elimination of gaskets and sealants; the elimination of fixing penetrations through the sheet and 99.9% UV protection with the protection coating co-extruded with the sheeting, eliminating any chance of delamination.

### 1.1 RESPONSIBILITIES

#### General

Requirement: Provide the DANPALON polycarbonate roof glazing system, as documented.

*Documented* is defined in *0171 General requirements* as meaning contained in the contract documents.

#### Ambient climatic conditions

Design rainfall intensity (mm/h) to AS/NZS 3500.3 (2021): [complete/delete]

See AS/NZS 3500.3 (2021) Appendix D for selected place references or the Hydrometeorological Advisory Services of the Bureau of Meteorology (HAS) at [www.bom.gov.au](http://www.bom.gov.au) for rainfall data.

#### Roof access

Requirement: To *0193 Building access safety systems*.

Document in *0193 Building access safety systems* if part of a building access installation to AS 1657 (2018).

### 1.2 COMPANY CONTACTS

#### DANPALON technical contacts

Website: [danpal.com.au/contact-us](http://danpal.com.au/contact-us)

### 1.3 CROSS REFERENCES

#### General

Requirement: Conform to the following:

- *0171 General requirements*.

*0171 General requirements* contains umbrella requirements for all building and services worksections.

List the worksections cross referenced by this worksection. *0171 General requirements* references the *018 Common requirements* subgroup of worksections. It is not necessary to repeat them here. However, you may also wish to direct the contractor to other worksections where there may be work that is closely associated with this work.

NATSPEC uses generic worksection titles, whether or not there are branded equivalents. If you use a branded worksection, change the cross reference here.

- *0193 Building access safety systems*.

### 1.4 STANDARDS

#### General

Design and installation: To AS 1562.3 (2006).

Polycarbonate: To AS 4256.5 (2006).

## 1.5 MANUFACTURER'S DOCUMENTS

### Technical manuals

Brochures: [danpal.com.au/brochures](http://danpal.com.au/brochures)

Design details: [danpal.com.au/resources/technical-documentation](http://danpal.com.au/resources/technical-documentation)

Colour properties: [danpal.com.au/colour](http://danpal.com.au/colour)

Warranties: [danpal.com.au/resources/technical-documentation](http://danpal.com.au/resources/technical-documentation)

Further information and sample orders: [danpal.com.au/contact-us](http://danpal.com.au/contact-us)

## 1.6 INTERPRETATION

### Abbreviations

General: For the purposes of this worksection, the following abbreviations apply:

- LT%: The percentage of visible light transmission (400 to 700 nm).
- SHGC: Solar heat gain coefficient.
- SR%: The percentage of total solar reflection (300 to 2800 nm).
- ST%: The percentage of total solar radiation transmission (300 to 2800 nm).

Edit the **Abbreviations** subclause to suit the project or delete if not required. List alphabetically.

## 1.7 SUBMISSIONS

### Fire hazard properties

Requirement: Submit evidence of conformance to **TRANSLUCENT PANEL SYSTEMS GENERALLY, Fire hazard properties**.

### Operation and maintenance manuals

Requirement: Submit manual to **COMPLETION, Operation and maintenance manuals**.

### Products and materials

Type tests: Submit test results for the following:

- Plastic sheet roofing: To **PRODUCTS, GENERAL, Tests**.

Type tests are carried out off-site. However, submission of evidence of a successful type test may be called up here for requirements specified in **PRODUCTS**.

A CodeMark Certificate of Conformity may be used as evidence of product conformity. See CodeMark Certificate of Conformity for conditions and limitations of the certificate.

### Samples

Requirement: Submit samples to **PRODUCTS, GENERAL, Samples**.

### Warranties

Requirement: Submit warranties to **COMPLETION, Warranties**.

## 1.8 INSPECTION

### Notice

Inspection: Give notice so that the framing and anchor points may be inspected before they are covered up or concealed.

Edit to suit the project, adding critical stage inspections required.

**Hold points**, if required, should be inserted here.

## 2 PRODUCTS

### 2.1 GENERAL

#### Product substitution

Other products: Conform to **SUBSTITUTIONS** in *0171 General requirements*.

**SUBSTITUTIONS** in *0171 General requirements* sets out the submissions required if the contractor proposes alternative products. Refer also to NATSPEC TECHnote GEN 006 for more information on proprietary specification.

**Samples**

Approved samples that define the acceptable limits of colour and texture variations are retained on site. If particular or additional samples are required, list them here.

Requirement: Provide samples of the roof glazing material, showing the range of variation available.

**Storage and handling**

Storage: To the Danpal's recommendations and as follows:

- Keep clean, dry and unexposed to weather.
- Protect from building materials and loose debris such as wet plaster, mortar, paint and welding splatter.
- Do not drag sheets or panels across each other or over other materials.
- Store off the ground, in sealed unopened packaging on a slightly sloped surface to prevent ponding on panel faces.

Storage area conditions: Allocate a safe and trade free area.

**Product identification**

General: Marked to show the following:

- Manufacturer's identification.
- Product brand name.
- Product type.
- Quantity.
- Product reference code and batch number.
- Date of manufacture.

Edit the list to suit the project or delete if not required.

**Tests**

0171 General requirements defines different tests in **INTERPRETATION, Definitions.**

Plastic sheet roofing and fastenings:

- Resistance to wind forces: To AS 1562.3 (2006) Section 5.
- Resistance to impact: To AS 1562.3 (2006) Section 5.

**2.2 TRANSLUCENT PANEL SYSTEMS GENERALLY**

For atrium roofs, refer to BCA (2022) G3 to determine if the atrium roof requires sprinkler protection.

Framed and glazed roofing may be a better option to accommodate sprinklers.

**DANPALON systems**

Description: Proprietary polycarbonate glazing system comprising polycarbonate panels, associated aluminium or polycarbonate connecting profiles and other framing accessories.

Certification: CodeMark Certificate No. CM20115.

The date of expiry of this CodeMark Certificate of Conformity is 14/12/2025.

See CodeMark Certificate of Conformity for conditions and limitations. To confirm it has not been withdrawn, suspended or superseded by later issue, see [register.jasanz.org/codemark-register](https://register.jasanz.org/codemark-register) for the CodeMark Register of Certificates of Conformity.

**Fire hazard properties**

Requirement: Conform to the following, tested to AS/NZS 1530.3 (1999).

- Ignitability Index: 0.
- Spread-of-flame Index: 0.
- Heat evolved: 0.
- Smoke-Developed Index: Maximum 5.

Test results for Ignitability, Spread-of-flame, Heat evolved and Smoke-Developed indices are available in the **Technical manuals.**

Group number: To AS 5637.1 (2015).

Most Danpal products have been tested for group number to AS ISO 9705 (2003) and achieve a group number of 1. Contact Danpal for more information.

Non-sprinklered buildings: Wall and ceiling linings must either have an average specific extinction area less than 250 m<sup>2</sup>/kg or a *smoke growth rate index* not more than 100 as determined by AS 5637.1 (2015).

Refer to NATSPEC TECHnote DES 020 for information on fire hazard properties.

### 2.3 SOLID TRANSPARENT PANELS (OVER SUBFRAME)

Detail the subframe to your office documentation policy. It is not provided by DANPALON.

#### General

Panel product: DANPALON 4 mm compact polycarbonate.

System description: Proprietary polycarbonate glazing system comprising solid polycarbonate panels, associated aluminium/polycarbonate connecting profiles and other framing accessories.

### 2.4 MULTIWALL TRANSLUCENT PANELS (OVER SUBFRAME)

Detail the subframe to your office documentation policy. It is not provided by DANPALON.

#### General

Panel product: DANPALON Honeycomb and Multicell polycarbonate (various thicknesses).

System description: Proprietary polycarbonate glazing system comprising multiwall polycarbonate panels, associated aluminium/polycarbonate connecting profiles and other framing accessories.

### 2.5 PROPRIETARY STRUCTURAL SYSTEM - FREESPAN RAFTER SYSTEM

To suit solid or multiwall DANPALON systems.

#### General

Product: Freespan Rafter system.

System description: Proprietary aluminium curved or straight structural system that supports all types of DANPALON panels, with structural accessories to suit.

### 2.6 PROPRIETARY STRUCTURAL SYSTEM - SOLARSPACE FRAMELESS SYSTEM

Suitable for use with 8 mm, 10 mm, 12 mm, 16 mm and 22 mm DANPALON panels. Available either curved or straight with structural accessories to suit.

#### General

Product: Solarspace aluminium framing system.

System description: Proprietary aluminium structural system with connectors above the panels.

### 2.7 PROPRIETARY STRUCTURAL SYSTEM – SEAMLESS ROOF SYSTEM

Suitable for use with all DANPALON Honeycomb or Multicell panels, except 8 mm. Available either curved or straight with structural accessories to suit.

#### General

Product: Seamless aluminium framing system.

System description: Proprietary aluminium structural system with connectors beneath the panels.

### 2.8 PROPRIETARY STRUCTURAL SYSTEM – DANPALON SPACE TRUSS™ SYSTEM

Suitable for use with all DANPALON Honeycomb or Multicell panels. Applicable to large, free-spanning canopies up to 45 metres. Available either curved or straight with structural accessories to suit.

Typically, the trusses are spaced 1.04 metres apart to suit the width of DANPALON light transmitting glazing panels. This glazing can be above the trusses, below them or on both sides, depending on visual preference and insulation requirements. Alternatively, any other roofing material can be installed by using special concealed brackets to attach purlins onto trusses up to 3.0 metres apart. The trusses are attached to the beams with special brackets that cater for free lateral thermal movement, resulting in a floating system with no stress on the materials.

The base support member is fixed to the beam, while the brackets holding the trusses can slide left or right, as required. The sliding brackets allow for movement in the trusses as well as accommodating a wide range of different shaped structures. By allowing the connection points to be adjustable, exact precision in locating the brackets and trusses during installation is not required.

#### General

Product: Space Truss™ system.

System description: Proprietary steel aluminium framing system.

### 3 EXECUTION

#### 3.1 PREPARATION

##### Substrate tolerance

Industry standards: [complete/delete]

Light steel framing: To NASH-1 (2005) Appendix D and NASH-2 (2014) Appendix A, cited in 0342 *Light steel framing*.  
 Structural steel: To AS/NZS 5131 (2016), cited in 0341 *Structural steelwork*. AS/NZS 5131 (2016) Section 12 and Appendix F cover tolerances.  
 Concrete: To the **Flatness tolerance class table** in either 0310 *Concrete - combined* or 0315 *Concrete finishes*.

#### 3.2 INSTALLATION

##### DANPALON requirements

Cutting and assembly: To the DANPALON installation specification.

#### 3.3 COMPLETION

##### Cleaning

General: To Danpal's cleaning instructions.

##### Operations and maintenance manuals

Requirement: Prepare a manual that includes DANPALON's recommendations for the maintenance of the roofing system including, frequency of inspection and recommended methods of access, inspection, cleaning, repair and replacement.

Compliance with this subclause targets the Operations and Maintenance requirement within the Minimum Expectation level of the Verification and Handover credit in Green Star Buildings (2021).

##### Warranties

Translucent panel systems: Provide DANPALON's published product warranties.

Refer to 0171 *General requirements* for appropriate warranty type and the terms covered in the warranty.

### 4 SELECTIONS

**Schedules** are a tool to specify properties required for products or systems. If the principal permits documentation of the product or system by proprietary name, some of the properties may be unnecessary and can be deleted. Document the product or system's location or application here and/or on the drawings with a matching project code. Refer to NATSPEC TECHnote GEN 024 for guidance on using and editing schedules.

Complete or delete the following subclauses as appropriate for the project.

#### 4.1 SOLID TRANSLUCENT PANELS

##### Solid transparent panels (over subframe)

Support system: [complete/delete]

Describe the support system or detail the subframe to your office documentation policy. It is not provided by DANPALON.

Panel lengths: Up to 12 000 mm.

Longer lengths panels available to order, subject to lead time.

Installed module width: 600 mm.

U-Value: 5.36 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

Select from the following stocked colours:

- Reflective Grey.
- Grey.
- Clear.

Other colours are available to order, subject to lead time. Refer to Danpal for the optical and solar properties, including the LT%, ST%, SR% and SHGC for each colour.

## 4.2 MULTIWALL TRANSLUCENT PANELS (OVER SUBFRAME)

### General

Support system: [complete/delete]

Describe the support system or detail the subframe to your office documentation policy. It is not provided by DANPALON.

### 8 mm Honeycomb panels

Panel lengths: Up to 12 000 mm.

Longer lengths are panels are available to order, subject to lead time.

Installed module width:

- With fasteners: 602 mm.

U-Value: 2.46 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

Select from the following stocked colours:

- Reflective Grey.
- Reflective Ice.
- Opal.
- Clear.

Other colours are available to order, subject to lead time. Refer to DANPALON for the optical and solar properties, including the LT%, ST%, SR% and SHGC for each colour.

### 10 mm Honeycomb panels

Panel lengths: Up to 12 000 mm.

Longer lengths panels are available to order, subject to lead time.

Installed module width:

- Without fasteners: 600 mm.

- With fasteners: 602 mm.

U-Value: 2.11 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

Select from the following colours:

- Reflective Grey.
- Opal.
- Bronze.
- Grey.
- Ice.
- Blue.
- Green.
- Clear.
- Amber.
- Purple.
- Red.
- Yellow.
- Dark Opal.

Refer to Danpal for the optical and solar properties, including the LT%, ST%, SR% and SHGC for each colour.

### 12 mm Honeycomb panels

Panel lengths: Up to 12 000 mm.

Installed module width:

- Without fasteners: 900 mm.

- With fasteners: 902 mm.

U-Value: 1.84 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

Select from the following stocked colours:

- Reflective Grey.
- Ice with Softlite.

### 16 mm Multicell panels

Panel lengths: Up to 12 000 mm.

Longer lengths panels are available to order, subject to lead time.

Width: [complete/delete]

Select from 600 mm or 1040 mm. 900 mm wide panels are available, subject to minimum quantities and lead time. Reflective Grey has a 1050 mm installed module because a 10 mm spacer is installed between the panels.

U-Value: 1.53 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

Select from the following stocked colours:

- Reflective Grey.
- Ice (with or without Softlite).
- Opal.
- Clear.

Other colours are available to order, subject to lead time.

Refer to DANPALON for the optical and solar properties, including the LT%, ST%, SR% and SHGC for each colour.

### 22 mm Multicell panels (3D Lite)

Panel lengths: Up to 12 000 mm.

Subject to minimum quantities and lead time.

Width: 600 mm.

U-Value: 1.75 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

Stocked colour is white. All other colours are available to order, subject to lead time.

### 35 mm Multicell panels

Panel lengths: [complete/delete]

All panels are made to order, subject to minimum quantities and lead time.

Width: 900 mm.

U-Value: 1.2 W/(m<sup>2</sup>.K).

Colour: [complete/delete]

All colours are available to order, subject to minimum quantities and lead time.

### System components

Support system: [complete/delete]

Refer to the DANPALON span table to determine subframe requirements as applicable.

Connectors: [complete/delete]

Polycarbonate:

- DPAC: Standard connector. Available in lengths up to 12 000 mm.
- DPACW: Wide connector for 16 mm Reflective Grey 1040 mm wide panels. Available in lengths up to 12 000 mm.

Aluminium:

- DPAC30: Standard connector. Available in lengths up to 7000 mm.
- DPAC54: Heavy duty connector. Available in lengths up to 7000 mm.
- DPACH: H connector for double glazed systems. Available in lengths up to 7000 mm.

For other connector options, see **PROPRIETARY STRUCTURAL SYSTEM – SEAMLESS ROOF SYSTEM**.

Connector caps to seal off the ends of the connectors: [complete/delete]

Select from the following:

- DPECC: Polycarbonate connector end cap.
- DPACEC: Aluminium connector end cap.



Aluminium F sections to seal off the sides of the roof area: [complete/delete]

Select from the following:

- DPAFS: 8 mm, 10 mm or 16 mm to suit panels.

Panel caps to seal off the ends of the panels: [complete/delete]

Select from the following:

- DPAEC: Aluminium panel end cap, for high end of panels.
- DPAPEC: Aluminium pivot panel end cap, for low end of panels.

Fastener fixing centres: [complete/delete]

Determine the fastener centres by the spanning capability of the panels and connectors specified, with reference to the DANPALON span table.

#### 4.3 PROPRIETARY STRUCTURAL SYSTEM - FREESPAN RAFTER SYSTEM

Complete or delete this clause as appropriate for the project.

##### General

DANPALON panels: [complete/delete]

Select from all DANPALON Honeycomb or Multicell panels except 22 mm and 35 mm.

Application: All DANPALON panels, except 22 mm and 35 mm.

##### Straight or curved aluminium rafters

DP Bars: [complete/delete]

Select from the following:

- DPAB60: For 4 mm, 8 mm or 10 mm panels.
- DPAB70: For 4 mm, 8 mm or 10 mm panels.
- DPAB80: For 10 mm or 12 mm panels.
- DPAB50: For 16 mm panels.
- DPAB100: For 16 mm panels.
- DPAB150: For 16 mm panels.

#### 4.4 PROPRIETARY STRUCTURAL SYSTEM – SOLARSPACE FRAMELESS SYSTEM

Complete or delete this clause as appropriate for the project.

##### Solarspace frameless system

Panel type: [complete/delete]

Connector type: [complete/delete]

Select from the following:

- DPAC60: 60 mm connector. Available in lengths up to 7000 mm.
- DPAC80: 80 mm connector. Available in lengths up to 7000 mm.
- DPAC100: 100 mm connector. Available in lengths up to 9000 mm.
- DPAC150: 150 mm connector. Available in lengths up to 9000 mm.

#### 4.5 PROPRIETARY STRUCTURAL SYSTEM – SEAMLESS ROOF SYSTEM

Complete or delete this clause as appropriate for the project.

##### General

DANPALON panel type: [complete/delete]

Select from DANPALON Honeycomb or Multicell panels.

DANPALON panel thickness: [complete/delete]

Select from 10 mm, 12 mm, 16 mm, 22 mm and 35 mm.

##### Connectors

Material: Aluminium.

Type: [complete/delete]

Select from the following:

- DPAC40: 40 mm connector. Available in lengths up to 7000 mm.
- DPAC50: 50 mm connector. Available in lengths up to 7000 mm.
- DPAC60: 60 mm connector. Available in lengths up to 7000 mm.
- DPAC70: 70 mm connector. Available in lengths up to 7000 mm.
- DPAC80: 80 mm connector. Available in lengths up to 7000 mm.
- DPAC100: 100 mm connector. Available in lengths up to 9000 mm.
- DPAC150: 150 mm connector. Available in lengths up to 9000 mm.

#### 4.6 PROPRIETARY STRUCTURAL SYSTEM – DANPALON SPACE TRUSS™ SYSTEM

Complete or delete this clause as appropriate for the project.

##### General

DANPALON panels: [complete/delete]

Select from DANPALON Honeycomb or Multicell panels.

DANPALON panel thickness: [complete/delete]

Select from 8 mm, 10 mm, 12 mm, 16 mm, 22 mm and 35 mm.

Other panels: [complete/delete]

Other roofing material can be installed by using special concealed brackets to attach purlins onto trusses up to 3.0 metres apart, e.g. profiled metal roofing, insulated metal roofing..

##### Connectors

Material: Aluminium.

Type: [complete/delete]

Select from the following:

- DPATC: Truss connector for panels either above or below the trusses.
- DPATB: Truss bar for panels above the trusses.
- DPATBS: Truss box section for non-DANPALON panels or trusses with purlins.

##### REFERENCED DOCUMENTS

The following documents are incorporated into this worksection by reference:

AS 1530		Methods for fire tests on building materials, components and structures
AS/NZS 1530.3	1999	Simultaneous determination of ignitability, flame propagation, heat release and smoke release
AS 1562		Design and installation of sheet roof and wall cladding
AS 1562.3	2006	Plastic
AS/NZS 3500		Plumbing and drainage
AS/NZS 3500.3	2021	Stormwater drainage
AS 4256		Plastic roof and wall cladding materials
AS 4256.5	2006	Polycarbonate
AS 5637		Determination of fire hazard properties
AS 5637.1	2015	Wall and ceiling linings
CM20115	2022	Danpalon Polycarbonate Wall and Roof Systems

The following documents are mentioned only in the **Guidance** text:

AS/NZS 1170		Structural design actions
AS/NZS 1170.3	2003	Snow and ice actions
AS 1657	2018	Fixed platforms, walkways, stairways and ladders - Design, construction and installation
AS/NZS 5131	2016	Structural steelwork - Fabrication and erection
AS ISO 9705	2003	Fire tests - Full-scale room test for surface products
HB 106	1998	Guidelines for the design of structures in snow areas
BCA G3	2022	Ancillary provisions - Atrium construction
GBCA Buildings	2021	Green Star Buildings
NASH		NASH Standard residential and low-rise steel framing
NASH-1	2005	Design criteria
NASH-2	2014	Design solutions
NATSPEC DES 004		Air, moisture and condensation
NATSPEC DES 020		Fire behaviour of building materials and assemblies
NATSPEC GEN 006		Product specifying and substitution
NATSPEC GEN 024		Using NATSPEC selections schedules
NATSPEC TR 01		Specifying ESD