

## 0429P PALRAM ROOFING - GLAZED

**Branded worksection**

This branded worksection *Template* has been developed by NATSPEC in conjunction with **PALRAM AUSTRALIA** (the Product Partner) and may be used whilst the Product Partner is licensed to distribute it. The copyright remains with NATSPEC. As with all NATSPEC worksections, it is the responsibility of the user to make sure it is completed appropriately for the project. The user should also review its applicability for local conditions and regulations. Check [www.natspec.com.au](http://www.natspec.com.au) for the latest updated version.

**Worksection abstract**

This branded worksection *Template* is applicable to PALRAM roof glazing and glazed awning systems by PALRAM Industries Limited.

**How to use this worksection**

Customise this worksection *Template* for each project. See [A guide to NATSPEC worksections \(www.natspec.com.au\)](#) for information on *Template* structure, word styles and completing a worksection.

**Related material located elsewhere in NATSPEC**

If a listed worksection is not part of your subscription package and you wish to purchase it, contact NATSPEC.

Related material may be found in other worksections, including:

- 0193 *Building access safety systems*.
- 0341 *Structural steelwork*.
- 0342 *Light steel framing* for the subframe.
- 0343 *Tensioned membrane structures* for suspended fabric roofing.
- 0411 *Waterproofing - external and tanking* for membrane roofs.
- 0461 *Glazing* for glass roofing and skylights.
- 0552 *Metalwork - fabricated* for ladders, platforms and balustrades.
- 0802 *Hydraulic design and install* for stormwater and rainwater storage systems.

Each of the following worksections contains a single roofing system and may be used if appropriate in addition to this worksection:

- 0423 *Roofing - profiled sheet metal*.
- 0424 *Roofing - seamed sheet metal*.
- 0425 *Roofing - shingles and shakes*.
- 0426 *Roofing - slate*.
- 0427 *Roofing - tiles*.
- 0428 *Roofing - insulated panel systems*.

Related branded worksections include:

- 0434p *PALRAM translucent facade cladding*.

**Documenting this and related work**

You may document this and related work as follows:

- Locate the extent of roofing types, accessories, and finishes on drawings to your office documentation policy.
- Penetrations: Show on the drawings the location and extent of penetrations for services and structural elements including flashing details.
- Document the structural support system to your office documentation policy.
- Contact PALRAM for limits of panel length and span tables.
- Coordinate the glazed roofing with any supporting structure and framing designed by a structural engineer.
- Show rooftop walkways, ladders and access systems on the drawings. Document in 0193 *Building access safety systems* if part of a complete building access installation to AS 1657 (2018).
- Show on the drawings the arrangement of the rainwater plumbing system, including the type and size of the main components (e.g. gutters, downpipes, sumps and rainheads) and the size and spacing of supports and fixings. In high wind areas, consider the degree of exposure of gutters and downpipes and the need to provide additional fixings.
- If documenting stormwater disposal, internal downpipes, rainwater tank and related products, use 0802 *Hydraulic design and install*.

- If documenting electric fan powered roof ventilators, document the necessary electrical connection in *0902 Electrical design and install*.
- If required, state the minimum thermal resistance (R-Value) (m<sup>2</sup>.K/W). See NATSPEC TECHnote DES 031 for information on specifying R-Values.
- If required, state the minimum thermal transmittance (U-Value) (W/(m<sup>2</sup>.K)). See NATSPEC TECHnote DES 031 for information on specifying thermal transmittance.
- For guidelines on the design of roofs in snow areas, see AS/NZS 1170.3 (2003) and HB 106 (1998).

The *Normal* style text of this worksection may refer to items as being documented elsewhere in the contract documentation. Make sure they are documented.

Search [acumen.architecture.com.au](http://acumen.architecture.com.au), the Australian Institute of Architects' practice advisory subscription service, for notes on the following:

- Birds and buildings.
- Guarantees and warranties.
- Site planning and design for bushfire.
- Waterproofing.

#### Specifying ESD

The following may be specified by including additional text:

- High performance roofing systems to extend building service life.
- High thermal performance to reduce heating/cooling load.
- Recycled material content.
- Recycling of construction scrap materials or offcuts. Polycarbonate is 100% recyclable.

Refer to NATSPEC TECHreport TR 01 on specifying ESD.

## 1 GENERAL

PALRAM is a world-leading manufacturer of extruded thermoplastic sheets and panel systems. With over 60 years of experience, a large portfolio of products, PALRAM is recognized as a leading brand for quality and service. PALRAM has grown into an industry leader and multinational conglomerate with branches on six continents. With added focus on advanced technologies and sustainability, PALRAM offers professionals and users the solutions and support they need for a wide variety of applications.

### 1.1 RESPONSIBILITIES

#### General

Requirement: Provide the PALRAM polycarbonate roof glazing system, with the necessary supports, trim, flashings, sealants and associated work, as documented.

*Documented* is defined in *0171 General requirements* as meaning contained in the contract documents.

#### Performance

Thermal qualities: Provide glazing with U-Value and Solar heat gain coefficient (SHGC), as documented.

#### Ambient climatic conditions

**Design rainfall intensity (mm/h) to AS/NZS 3500.3 (2021): [complete/delete]**

See AS/NZS 3500.3 (2021) Appendix D for selected place references or the Hydrometeorological Advisory Services of the Bureau of Meteorology (HAS) at [www.bom.gov.au](http://www.bom.gov.au) for rainfall data.

#### Roof access

Requirement: To *0193 Building access safety systems*.

Document in *0193 Building access safety systems* if part of a building access installation to AS 1657 (2018).

### 1.2 COMPANY CONTACTS

#### PALRAM technical contacts

Website: [palram.com.au/contact](http://palram.com.au/contact)

### 1.3 CROSS REFERENCES

#### General

Requirement: Conform to the following:

- 0171 General requirements.

0171 General requirements contains umbrella requirements for all building and services worksections.

List the worksections cross referenced by this worksection. 0171 General requirements references the 018 Common requirements subgroup of worksections. It is not necessary to repeat them here. However, you may also wish to direct the contractor to other worksections where there may be work that is closely associated with this work.

NATSPEC uses generic worksection titles, whether or not there are branded equivalents. If you use a branded worksection, change the cross reference here.

- 0193 Building access safety systems.

## 1.4 STANDARDS

### General

Design and installation: To AS 1562.3 (2006).

Polycarbonate: To AS 4256.5 (2006).

## 1.5 MANUFACTURER'S DOCUMENTS

### Technical manuals

Website: [palram.com.au/products](http://palram.com.au/products)

## 1.6 INTERPRETATION

### Abbreviations

General: For the purposes of this worksection, the following abbreviations apply:

- LT%: The percentage of visible light transmission.
- SC: Shading coefficient.
- SHGC: Solar heat gain coefficient.

Edit the **Abbreviations** subclause to suit the project or delete if not required. List alphabetically.

## 1.7 SUBMISSIONS

### Fire hazard properties

Requirement: Submit evidence of conformance to **PALRAM SYSTEMS GENERALLY, Fire hazard properties**.

### Operation and maintenance manuals

Requirement: Submit manual to **COMPLETION, Operation and maintenance manuals**.

### Products and materials

Type tests: Submit test results for the following:

- Plastic sheet roofing: To **PRODUCTS, GENERAL, Tests**.

Type tests are carried out off-site. However, submission of evidence of a successful type test may be called up here for requirements specified in **PRODUCTS**.

### Samples

Requirement: Submit samples to **PRODUCTS, GENERAL, Samples**.

### Shop drawings

Shop drawings are necessary if some or all of the system is to be designed by the contractor or a specialist subcontractor to meet the performance criteria specified. If this is not the case, delete **Shop drawings**.

Requirement: Submit shop drawings to a scale that best describes the detail, showing the following:

- Layout and arrangement of roof glazing panels.
- Connection to substructure.
- Edge restraint.
- Clearances and tolerances.
- Glazing gaskets and sealant beads.

### Subcontractors

Installers experience: Submit evidence of experience with glazed roofing installations.

### Tests

Detail the tests required in **EXECUTION** and list the submissions required here.

Watertightness: Submit test results to **TESTING, Watertightness tests**.

#### Warranties

Requirement: Submit warranties to **COMPLETION, Warranties**.

### 1.8 INSPECTION

#### Notice

Inspection: Give notice so that the framing and anchor points may be inspected before they are covered up or concealed.

Edit to suit the project, adding critical stage inspections required.

**Hold points**, if required, should be inserted here.

## 2 PRODUCTS

### 2.1 GENERAL

#### Product substitution

Other products: Conform to **SUBSTITUTIONS** in *0171 General requirements*.

**SUBSTITUTIONS** in *0171 General requirements* sets out the submissions required if the contractor proposes alternative products. Refer also to NATSPEC TECHnote GEN 006 for more information on proprietary specification.

#### Samples

Approved samples that define the acceptable limits of colour and texture variations are retained on site. If particular or additional samples are required, list them here.

Requirement: Provide samples of the following, showing the range of variation available:

- Glazing materials, each at least 200 x 200 mm, showing specified visual properties.
- Custom profiled flashings and cappings
- Trim and accessories with a colour finish.
- Sealants.

#### Storage and handling

Storage: To PALRAM's recommendations and as follows:

- Keep clean, dry and unexposed to weather.
- Protect from building materials and loose debris such as wet plaster, mortar, paint and welding splatter.
- Do not drag sheets or panels across each other or over other materials.
- Store off the ground, in sealed unopened packaging on a slightly sloped surface to prevent ponding on panel faces.

Storage area conditions: Allocate a safe and trade free area.

#### Product identification

General: Marked to show the following:

- Manufacturer's identification.
- Product brand name.
- Product type.
- Quantity.
- Product reference code and batch number.
- Date of manufacture.

Edit the list to suit the project or delete if not required.

#### Tests

*0171 General requirements* defines different tests in **INTERPRETATION, Definitions**.

Plastic sheet roofing and fastenings:

- Resistance to wind forces: To AS 1562.3 (2006) Section 5.
- Resistance to impact: To AS 1562.3 (2006) Section 5.

## 2.2 PALRAM SYSTEMS GENERALLY

For atrium roofs, refer to BCA (2022) G3 to determine if the atrium roof requires sprinkler protection.

Framed and glazed roofing may be a better option to accommodate sprinklers.

### General

Description: Proprietary polycarbonate glazing systems comprising polycarbonate panels, associated aluminium or polycarbonate connecting profiles and other framing accessories.

### Fire hazard properties

Requirement: Conform to the following, tested to AS/NZS 1530.3 (1999).

- Ignitability Index: 0.
- Spread-of-flame Index: 0.
- Heat evolved: 0.
- Smoke-Developed Index: Maximum 5.

Test results for Ignitability, Spread-of-flame, Heat evolved and Smoke-Developed indices are available at [palram.com.au/products](http://palram.com.au/products).

Group number: To AS 5637.1 (2015).

Some PALRAM products have been tested for group number to AS ISO 9705 (2003) and achieve a group number of 1. Contact PALRAM for more information.

Non-sprinklered buildings: Wall and ceiling linings must either have an average specific extinction area less than 250 m<sup>2</sup>/kg or a *smoke growth rate index* not more than 100 as determined by AS 5637.1 (2015).

Refer to NATSPEC TECHnote DES 020 for information on fire hazard properties.

## 2.3 PALRAM SUNGLAZE - SOLID TRANSPARENT PANELS (OVER SUBFRAME)

Detail the subframe to your office documentation policy. It is not provided by PALRAM.

### General

Panel product: PALRAM SUNGLAZE solid polycarbonate standing seam architectural system.

System description: Solid polycarbonate roof glazing system with standing seam and proprietary aluminium connection detail.

Cover width: 800 mm.

Thickness: 4 mm.

Nominate colour, profile, thickness, connectors, accessories and performance requirements in SELECTIONS, **PALRAM SUNGLAZE - Solid transparent panels**.

## 2.4 PALRAM EZ-GLAZE - SOLID TRANSPARENT PANELS (OVER RAFTERS)

Detail the subframe to your office documentation policy. It is not provided by PALRAM.

### General

Panel product: PALRAM EZ-Glaze, solid polycarbonate roof sheet.

System description: Solid, flat polycarbonate glazing panels with profiled edge for lapping and fixing directly over rafters.

Cover width: 600 mm.

Thickness: 3 mm.

Nominate length, colour and accessories in SELECTIONS, **PALRAM SUNTUF EZ-Glaze - Flat transparent panels**.

## 2.5 PALRAM SUNPAL - MULTIWALL TRANSLUCENT PANELS (OVER SUBFRAME)

Detail the subframe to your office documentation policy. It is not provided by PALRAM.

### General

Panel product: PALRAM SUNPAL multiwall polycarbonate standing seam architectural system.

System description: Proprietary polycarbonate system comprising multicell polycarbonate thermal/acoustic rated panels with associated aluminium/polycarbonate standing seam connecting profiles, support rafters and other framing accessories.

Nominate colour, thickness, connectors, accessories and performance requirements in SELECTIONS, **PALRAM SUNPAL - Multiwall translucent panels**.

## 2.6 PALRAM DURASHIELD - NON-CORROSIVE PROFILED PVC SHEET

Detail the subframe to your office documentation policy. It is not provided by PALRAM.

### General

Panel product: PALRAM DURASHIELD industrial profiled PVC roof sheet.

System description: Proprietary profiled opaque PVC sheet for industrial applications with superior chemical, fire and impact resistance.

Nominate colour, profile, thickness, connectors and performance requirements in SELECTIONS, **PALRAM DURASHIELD - Profiled PVC sheet**.

## 2.7 SUNTUF PROFILED INDUSTRIAL SHEET

Detail the subframe to your office documentation policy. It is not provided by PALRAM.

### General

Panel product: PALRAM SUNTUF profiled polycarbonate sheet.

System description: Proprietary profiled polycarbonate sheet suitable for industrial applications, with superior impact resistance and high light transmission rates. Available in hundreds of profiles to match metal profiles.

Nominate colour, profile, thickness, connectors and performance requirements in SELECTIONS, **PALRAM SUNTUF - Profiled transparent panels**.

## 2.8 SUNTUF BEEHIVE

Detail the subframe to your office documentation policy. It is not provided by PALRAM.

### General

Panel product: PALRAM BEEHIVE corrugated polycarbonate sheet.

System description: Proprietary profiled polycarbonate sheet, with diffused light transmission and prismatic obscure finish.

Nominate colour, connectors and performance requirements in SELECTIONS, **PALRAM SUNTUF - Profiled transparent panels**.

## 3 EXECUTION

### 3.1 GENERAL

#### Preparation

Substrates or framing: Before fixing roofing, check the alignment of substrates or framing and correct centre spacings and adjust if required.

Industry standards: [complete/delete]

Light steel framing: To NASH-1 (2005) Appendix D and NASH-2 (2014) Appendix A, cited in *0342 Light steel framing*.

Structural steel: To AS/NZS 5131 (2016), cited in the *0341 Structural steelwork*. AS/NZS 5131 (2016) Section 12 and Appendix F cover tolerances.

Concrete: To the **Flatness tolerance class table** in either *0310 Concrete - combined* or *0315 Concrete finishes*.

### 3.2 INSTALLATION

#### PALRAM requirements

Cutting and assembly: To the PALRAM installation details.

Support system: [complete/delete]

Subframe by others. Document on architectural drawings or to structural engineers details.

**ROOF PLUMBING** and **ROOF VENTILATORS** are not included in this worksection. Import text from *0420 Roofing - combined* if required.

#### Protection

General: Keep the roofing and rainwater system free of debris and loose material during construction.

Protection: Protect surfaces and finishes, including the retention of protective coatings during installation.

**Thermal movement**

Requirement: Allow for thermal movement in the roof installation and the structure, including movement in joints and fastenings.

**Metal separation**

Make sure of compatibility or detail separation.

See AS 1562.1 (2018) Appendix C Table C3 for guidance on the compatibility of metals. See also SA HB 39 (2015) Section 2 on material selection. It is primarily a design responsibility that incompatible metals are not documented or shown to be in contact. Preferably show the separation method on the drawings.

Corrosion can result from water run-off between incompatible surfaces. See AS 1562.1 (2018) clause 3.4.3 and AS 1562.1 (2018) Appendix C Table C4. There are four conditions to be avoided:

- Run-off from copper and copper alloys onto aluminium, zinc, galvanized, or aluminium/zinc-coated surfaces.
- Run-off from glass onto stainless steel, zinc or galvanized surfaces.
- Run-off from plastic onto zinc or galvanized surfaces.
- Run-off from inert catchment surfaces such as glazed terracotta, prepainted steel, aluminium and aluminium/zinc onto zinc or galvanized surfaces.

In marine or high humidity environments, separate green hardwood from aluminium and coated steel.

Typical methods for metal separation include:

- Applying an anti-corrosion, low moisture transmission coating such as zinc or barium chromate primer or aluminium pigmented bituminous paint to contact surfaces.
- Inserting a separation layer such as polyethylene film, adhesive tape or bituminous felt.

Requirement: Prevent direct contact between incompatible metals, and between green hardwood or chemically treated timber and aluminium or coated steel, by one of the following methods:

- Applying an anti-corrosion, low moisture transmission coating to contact surfaces.
- Inserting a separation layer such as foam tape.

**3.3 TESTING**

0171 General requirements defines different tests in **INTERPRETATION**, **Definitions** and calls for an inspection and testing plan in **TESTING - GENERALLY**, **Inspection and testing plan**.

**Watertightness tests**

Glazed roofing: Test for watertightness after installation. If required, remedy defects and retest.

**3.4 COMPLETION****Cleaning**

General: To PALRAM's cleaning instructions.

**Operation and maintenance manuals**

Requirement: Prepare a manual that includes PALRAM's recommendations for the maintenance of the roofing system including, frequency of inspection and recommended methods of access, inspection, cleaning, repair and replacement.

Compliance with this subclause targets the Operations and Maintenance requirement within the Minimum Expectation level of the Verification and Handover credit in Green Star Buildings (2021).

**Warranties**

Refer to 0171 General requirements for appropriate warranty type and the terms covered in the warranty.

Type: Manufacturer's warranty.

Refer to **Warranty types** in 0171 General requirements.

Period: [complete/delete]

Refer to PALRAM for the warranties available for the particular system at [palram.com.au/products](http://palram.com.au/products).

**4 SELECTIONS**

**Schedules** are a tool to specify properties required for products or systems. If the principal permits documentation of the product or system by proprietary name, some of the properties may be unnecessary and can be deleted. Document the product or system's location or application here and/or on the drawings with a matching project code. Refer to NATSPEC TECHnote GEN 024 for guidance on using and editing schedules.



#### 4.1 PRODUCTS

##### PALRAM SUNGLAZE - Solid transparent panels

	A	B	C
Panel lengths			
Colour			
Light transmission (LT %)			
Solar heat gain (SHGC)			
Shading coefficient (SC)			
U-Value (W/(m <sup>2</sup> .K))			

The codes in the header row of the schedule designate each application or location of the item scheduled. Edit the codes to match those in other contract documents.

Panel lengths: Nominate length up to 12 m (longer lengths can be produced). Palram Australia hold 9 m lengths in stock.

Colour: Select from;

- Clear.
- Solar Grey.

Solar Smart range:

- Solar Ice.
- Solar Control Grey.
- Bluish Breeze.

Light transmission (LT): Subject to colour selected. Refer to PALRAM product details.

Solar heat gain coefficient (SHGC): Subject to colour selected. Refer to PALRAM product details.

Shading coefficient (SC): Subject to colour selected. Refer to PALRAM product details.

U-Value (W/(m<sup>2</sup>.K)): 5.29 W/(m<sup>2</sup>.K) for 4 mm thickness.

##### PALRAM SUNTUF EZ-Glaze - Flat transparent panels

	A	B	C
Panel lengths			
Colour			
Accessories			

The codes in the header row of the schedule designate each application or location of the item scheduled. Edit the codes to match those in other contract documents.

Panel lengths: Nominate length up to 7 m (special order for longer lengths).

Colour: Select from:

- Clear.
- Bluish Breeze.
- Grey.

Accessories: Nominate fixings, foam infills, purlin tape and project specific requirements. Refer to PALRAM product details.

##### PALRAM SUNPAL - Multiwall translucent panels

	A	B	C
Thickness			
Width			
Panel lengths			
Colour			
Light transmission (LT %)			
Solar heat gain (SHGC)			
Shading coefficient (SC)			
U-Value (W/(m <sup>2</sup> .K))			



	A	B	C
Joiners			
Accessories			

The codes in the header row of the schedule designate each application or location of the item scheduled. Edit the codes to match those in other contract documents.

Thickness: Select from: 10 mm, 18 mm and 20 mm (non-stocked thickness).

Width: Select from 600 mm or 1000 mm.

Panel lengths: Nominate length up to 11.980 m.

Colour: Select from:

- Clear.
- Solar Grey.
- Orange.
- Purple.
- Yellow.
- Magenta.
- Green.
- Bronze.
- White Opal.
- Red.
- Blue.

Solar Smart. Select from:

- Solar Ice.
- Solar Control Grey.
- Bluish Breeze.

Diffuser Plus colour. Select from:

- White Opal.
- Clear.
- Solar Ice.

Light transmission (LT): Subject to colour selected. Refer to PALRAM product details.

Solar heat gain coefficient (SHGC): Subject to colour selected. Refer to PALRAM product details.

Shading coefficient (SC): Subject to colour selected. Refer to PALRAM product details.

U-Value (W/(m<sup>2</sup>.K)): Nominate requirement here. Refer to PALRAM product details.

Joiners: Select from polycarbonate or aluminium.

Accessories: Nominate Spanbar aluminium rafters, fixings, foam infills, purlin tape and project specific requirements. Refer to PALRAM product details.

#### PALRAM DURASHIELD - Profiled PVC sheet

	A	B	C
Profile			
Panel lengths			
Thickness			
Colour			
Accessories			

The codes in the header row of the schedule designate each application or location of the item scheduled. Edit the codes to match those in other contract documents.

Profile: Select from:

- Corrugated (Industrial Wave).
- Trimdeck (Industrial Rib).
- Spandek (Greca Wide).

Panel lengths: Up to 9 m.

Thickness: Refer to PALRAM product details.

Colour: Select from White (opaque) or Beige (opaque).

Accessories: Nominate fixings, foam infills, purlin tape and project specific requirements. Refer to PALRAM product details.

#### **PALRAM SUNTUF - Profiled transparent panels**

	<b>A</b>	<b>B</b>	<b>C</b>
Product			
Panel finish			
Thickness			
Profile			
Panel lengths			
Colour			
Light transmission (LT %)			
Solar heat gain (SHGC)			
Shading coefficient (SC)			
U-Value (W/(m <sup>2</sup> .K))			
Accessories			

The codes in the header row of the schedule designate each application or location of the item scheduled. Edit the codes to match those in other contract documents.

Product: Select from the SUNTUF product range including:

- SUNTUF Industrial: For Industrial exterior applications, with high light transmission.
- SUNTUF Beehive: Corrugated, embossed polycarbonate sheet. Stronger Impact Resistance.

Panel finish. Select from:

- SUNTUF: Sheet with integrated UV protective layer on one side.
- SUNTUF Plus: Sheet with UV protective layer on external side and anti-condensation treatment to the interior side.
- SUNTUF SolarSmart: Transmits selected percentage of daylight and reflects and absorbs some of the heat generating infra-red radiation. Embossed underside dissipating the light.

Thickness: Refer to PALRAM product details.

Profile: Nominate the profile here.

Standard SUNTUF Industrial profiles:

- Corrugated.
- Trimdeck.
- Spandek.
- Kliplock.

Can be produced to match metal roofing profiles.

Panel lengths: Up to 12 m. Palram Australia hold 9 m lengths in stock.

Colour: Select from:

Transparent

- Clear.
- Solar Grey.
- Bronze.
- Transparent Grey.

Translucent

- White Opal.
- White Diffuser.
- Metallic Sandune.
- Metallic Jasper.
- Solar Control Grey.

- Solar Ice.
- Smooth Cream.

Light transmission (LT): Subject to colour selected. Refer to PALRAM product details.

Solar heat gain coefficient (SHGC): Subject to colour selected. Refer to PALRAM product details.

Shading coefficient (SC): Subject to colour selected. Refer to PALRAM product details.

U-Value (W/(m<sup>2</sup>.K)): Nominate requirement here. Refer to PALRAM product details.

Accessories: Nominate fixings, foam infills, purlin tape and project specific requirements. Refer to PALRAM product details.

#### REFERENCED DOCUMENTS

The following documents are incorporated into this worksection by reference:

AS 1530		Methods for fire tests on building materials, components and structures
AS/NZS 1530.3	1999	Simultaneous determination of ignitability, flame propagation, heat release and smoke release
AS 1562		Design and installation of sheet roof and wall cladding
AS 1562.3	2006	Plastic
AS/NZS 3500		Plumbing and drainage
AS/NZS 3500.3	2021	Stormwater drainage
AS 4256		Plastic roof and wall cladding materials
AS 4256.5	2006	Polycarbonate
AS 5637		Determination of fire hazard properties
AS 5637.1	2015	Wall and ceiling linings

The following documents are mentioned only in the **Guidance** text:

AS/NZS 1170		Structural design actions
AS/NZS 1170.3	2003	Snow and ice actions
AS 1562		Design and installation of sheet roof and wall cladding
AS 1562.1	2018	Metal
AS 1657	2018	Fixed platforms, walkways, stairways and ladders - Design, construction and installation
AS/NZS 5131	2016	Structural steelwork - Fabrication and erection
AS ISO 9705	2003	Fire tests - Full-scale room test for surface products
SA HB 39	2015	Installation code for metal roof and wall cladding
HB 106	1998	Guidelines for the design of structures in snow areas
BCA G3	2022	Ancillary provisions - Atrium construction
GBCA Buildings	2021	Green Star Buildings
NASH		NASH Standard residential and low-rise steel framing
NASH-1	2005	Design criteria
NASH-2	2014	Design solutions
NATSPEC DES 020		Fire behaviour of building materials and assemblies
NATSPEC DES 031		Specifying R-Values
NATSPEC GEN 006		Product specifying and substitution
NATSPEC GEN 024		Using NATSPEC selections schedules
NATSPEC TR 01		Specifying ESD